

'Apollo' Valves

SUBMITTAL SHEET

106T Series

Class 150, Non Rising Stem, NPT Gate Valve



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	



DESCRIPTION

The Apollo Model 106T (30 Series) Gate Valve provides a cost effective "Made in the USA" alternative to globally sourced multi-turn valves. These valves are cast, machined, assembled, and tested in South Carolina. The Apollo Gate Valve can reliably be installed in most plumbing and heating systems (or building service piping).

FEATURES

- Guided Solid Bronze Discs
- Adjustable Graphite Stem Packing
- Non Rising Stem
- Dezincification Resistant
- All Bronze Construction
- 100% Factory tested
- NPT Connection
- Screwed Bonnet
- Malleable Iron Rugged Hand Wheel
- 100% Cast, Machined and Assembled in the US
- ARRA Compliant

STANDARDS

- MSS SP-80, "Bronze Gate, Globe, Angle & Check Valves"
- ASME B1.20.1, "Pipe Threads, General Purpose (Inch)"
- Canadian Registration Number OC14667.5

PERFORMANCE RATING

- Saturated Steam: 150 psi (10.4 Bar) to 366°F (185°C)
 - Cold Working Pressure: 300 psi (20.7Bar) at 100°F
 - Temperature Range*: -20°F to 406°F
- * Valves should be in open position to allow complete drainage during freezing conditions.

STANDARD MATERIALS LIST

Part Name	Material
Body	ASTM B62 Bronze
Bonnet	ASTM B62 Bronze
Stem	ASTM B371 Bronze
Disc	ASTM B62 Bronze
Packing	Grafoil®
Packing Nut	ASTM B16 Brass
Hand Wheel	Malleable Iron
Nameplate	Aluminum

ORDER INFORMATION

Model Number	Part Number	Size (in.)
106T14	30-281-01	1/4"
106T38	30-282-01	3/8"
106T12	30-283-01	1/2"
106T34	30-284-01	3/4"
106T1	30-285-01	1"
106T114	30-286-01	1-1/4"
106T112	30-287-01	1-1/2"
106T2	30-288-01	2"
106T212	30-289-01	2-1/2"
106T3	30-280-01	3"

DIMENSIONS

Height open (in.)	Length (in.)	Weight (lbs)	Cv (gpm)
3.29	1.76	.74	3.0
3.29	1.76	.71	6.0
3.56	2.03	.98	12.5
4.05	2.07	1.21	24.0
4.55	2.45	1.98	72.3
5.14	2.63	2.8	80.0
6.02	2.88	4.06	119.0
7.09	3.06	5.88	338.0
9.11	4.13	12.19	395.0
12.61	4.48	16.90	435.0

Apollo Valves, Manufactured by **Conbraco Industries, Inc.**
 701 Matthews Mint-Hill Road, Matthews, NC 28105 USA
www.apollovalves.com | (704) 841-6000

This specification is provided for reference only. Conbraco Industries Inc. reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. Please visit our website @ www.apollovalves.com for the most current information.

